



NOTE: All relevant materials are complied with RoHS directive .

5	BLACK HEAT SHIRK TUBE $\phi 1.0 \times 10\text{mm}$	1	M743
	MOLDED PE COLOR TRANSPARENT		TWN
	MOLDED PVC BEIGE		M301
4	MOLDED PVC BEIGE		M304
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG,AMA BRAID DD 4.5mm, JACKET BEIGE, DRAWING No.EUAB2801P2402C-139	L-20mm	M304
2	USB A FEMALE 2.0, GOLD PLATING 30u" ON CONTACTS, WIIITE INSULATOR	1	M108
1	USB A MALE 2.0, GOLD PLATING 30u" ON CONTACTS, WHITE INSULATOR, SHORT TYPE	1	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED	PCCABLES.COM INC		Cable Length Unless Other Spec. Tolerances: 0 ~200mm $\pm 10\text{mm}$ 201~1000mm $\pm 20\text{mm}$ 1001 ~1500mm $\pm 25\text{mm}$ 1501~2100mm $\pm 30\text{mm}$ 2100mm \uparrow $\pm 40\text{mm}$
CHECKED	jfk		
DRAWING			
DATE	22/NOV/07	ITEM NO.	
CHECKED		UNIT:mm	